

NAME

pltotf – convert property list files to TeX font metric (tfm) format

SYNOPSIS

pltotf [**-verbose**] *pl_file_name*[**.pl**] [*tfm_file_name*[**.tfm**]]

DESCRIPTION

This manual page is not meant to be exhaustive. The complete documentation for this version of T_EX can be found in the info file or manual *Web2C: A TeX implementation*.

The **pltotf** program translates a (human-oriented) property list file to a (program-oriented) T_EX font metric file. Thus, after editing the property list file, a TFM file can be generated for use with, for example, **tex**(1).

The *pl_file_name* is extended with **.pl** if it lacks a suffix. No path searching is done.

If no *tfm_file_name* is given, the basename of *pl_file_name* with suffix **.tfm** is used; otherwise *tfm_file_name* is extended with **.tfm** if it lacks a suffix.

OPTIONS

Without the **-verbose** option, **pltotf** operates silently. With it, a banner and progress report are printed on *stdout*.

SEE ALSO

tftopl(1).

Donald E. Knuth, *T_EX for troffware*.

Donald E. Knuth, *The METAFONTbook*, (Volume C of *Computers and Typesetting*), Addison-Wesley, 1986, ISBN 0-201-13445-4.

AUTHORS

Donald E. Knuth wrote the program. It was published as part of the *T_EX for troffware* technical report, available from the T_EX Users Group. Howard Trickey, Pavel Curtis, and Richard Furuta originally ported it to Unix.