

# The l3build package

## Checking and building packages\*

The L<sup>A</sup>T<sub>E</sub>X3 Project<sup>†</sup>

Released 2015/07/28

## Contents

<b>1</b>	<b>The l3build system</b>	<b>1</b>	<b>2</b>	<b>Writing test files</b>	<b>12</b>
1.1	Introduction . . . . .	1	2.1	Metadata and structural commands . . . . .	13
1.2	Main build commands . . . .	3	2.2	Commands to help write tests	13
1.3	Example build scripts . . . .	6	2.3	Showing box content . . . . .	14
1.4	Variables . . . . .	7	2.4	Typesetting documentation .	15
1.5	Dependencies . . . . .	9			
1.6	Output normalisation . . . .	11			
1.7	Generating test files with DocStrip . . . . .	12			
				<b>Index</b>	<b>17</b>

## 1 The l3build system

### 1.1 Introduction

The l3build system is a Lua script for building T<sub>E</sub>X packages, with particular emphasis on regression testing. It is written in cross-platform Lua code, so can be used by any modern T<sub>E</sub>X distribution with the `texlua` interpreter. A package for building with l3build can be written in any T<sub>E</sub>X dialect; its defaults are set up for L<sup>A</sup>T<sub>E</sub>X packages written in the DocStrip style. (Caveat: minimal testing has yet been performed for non-L<sup>A</sup>T<sub>E</sub>X packages.)

Test files are written as standalone T<sub>E</sub>X documents using the `regression-test.tex` setup file; documentation on writing these tests is discussed in Section 2.

The `l3build.lua` script is not designed to be executed directly; each package will define its own `build.lua` script as a driver file which both sets variables (such as the name of the package) and then calls the main `l3build.lua` script internally.

---

\*This file describes v5704, last revised 2015/07/28.

<sup>†</sup>E-mail: [latex-team@latex-project.org](mailto:latex-team@latex-project.org)

A standard package layout might look something like the following:

```
abc/
  abc.dtx
  abc.ins
  build.lua
  README.md
  support/
  testfiles/
```

Most of this should look fairly self-explanatory. The top level **support/** directory (optional) would contain any necessary files for compiling documentation, running regression tests, and so on.

The **l3build** system is also capable of building and checking *bundles* of packages. To avoid confusion, we refer to either a standalone package or a package within a bundle as a *module*.

For example, within the L<sup>A</sup>T<sub>E</sub>X3 project we have the **l3packages** bundle which contains the **xparse**, **xtemplate**, etc., modules. These are all built and distributed as one bundle for installation, distribution *via* CTAN and so forth.

Each module in a bundle will have its own build script, and a bundle build script brings them all together. A standard bundle layout would contain the following structure.

```
mybundle/
  build.lua
  support/
  yyy/
    build.lua
    README.md
    testfiles/
    yyy.dtx
    yyy.ins
    zoo/
      build.lua
      README.md
      testfiles/
      zoo.dtx
      zoo.ins
```

All modules within a bundle must use the same build script name.

In a small number of cases, the name used by CTAN for a module or bundle is different from that used in the installation tree. For example, the L<sup>A</sup>T<sub>E</sub>X2<sub>ε</sub> kernel is called **latex-base** by CTAN but is located inside  $\langle texmf \rangle / tex / latex / base$ . This can be handled by using **ctanpkg** for the name required by CTAN to override the standard value.

The **testfiles/** folder is local to each module, and its layout consists of a series of regression tests with their outputs.

```
testfiles/
  test1.lvt
  test1.tlg
  ...
  support/
    my-test.cls
```

Again, the **support/** directory contains any files necessary to run some or all of these tests.

When the build system runs, it creates a directory **build/** for various unpacking, compilation, and testing purposes. For a module, this build folder can be in the main directory of the package itself, but for a bundle it should be common for the bundle itself and for all modules within that bundle. A **build/** folder can be safely deleted; all material within is re-generated for each command of the **l3build** system.

## 1.2 Main build commands

In the working directory of a bundle or module, the following commands can be executed:

- **check**
- **check** *<name>* [*<engine>*]
- **cmdcheck**
- **clean**
- **doc**
- **install**
- **save** *<name>* [*<engine>*]

These commands are described below.

```
$ texlua build.lua check
```

The **check** command runs the entire test suite. This involves iterating through each **.lvt** file in the test directory (specified by the **testfiledir** variable), compiling each test in a “sandbox” (a directory specified by **testdir**), and comparing the output against each matching predefined **.tlg** file.

If changes to the package or the typesetting environment have affected the results, the check for that file fails. A **diff** of the expected to actual output should then be inspected to determine the cause of the error; it is located in the **testdir** directory (default **maindir .. "/build/test"**).

The following files are moved into the “sandbox” for the **check** process:

- all **installfiles** after unpacking;
- all **checkfiles** after unpacking;
- any files in the directory **testsuppdir**;
- any files that match **checksuppfiles** in the **supportdir**.

This range of possibilities allow sensible defaults but significant flexibility for defining your own test setups.

Checking can be performed with any or all of the ‘engines’ **pdftex**, **xetex**, and **luatex**. By default, each test is executed with all three, being compared against the **.tlg** file produced from the **pdftex** engine (these defaults are controlled by the **checkengines** and **stdengine** variable respectively). The format used for tests can be altered by setting **checkformat**: the default setting **latex** means that tests are run using *e.g.* **pdflatex**,

whereas setting to `plain` will run tests using *e.g.* `pdftex`. (Currently, this should be one of `latex` or `plain`.) To perform the check, the engine typesets each test `checkruns` times. More detail on this in the documentation on `save`. Options passed to the binary are defined in the variable `checkopts`.

By default, `texmf` trees are searched for input files when checking. This can be disabled by setting `checksearch` to `false`: isolation provides confidence that the tests cannot accidentally be running with incorrect files installed in the main distribution or `hometexmf`.

```
$ texlua build.lua check <name> [<engine>]
```

Checks only the test `<name>.lvt` with optionally specified `<engine>` (one of `pdftex`, `xetex`, or `luatex`). If an `<engine>` is not specified, all three engines are checked (or those defined by the `checkengines` variable if changed from the default).

```
$ texlua build.lua cmdcheck
```

For `l3doc`-based sources, allows checking that the commands defined in the code part (by `cmdchkfiles`) are documented in the description part. This is performed by passing the `check` option to the `l3doc` class, typesetting the file(s) to check with engine `stdengine` with options `cmdchkopts`, and checking the resultant `.cmds` file(s). Dependencies are specified also with `checkdeps`.

```
$ texlua build.lua clean
```

This command removes all temporary files used for package bundling and regression testing. In the standard layout, these are all files within the directories defined by `localdir`, `testdir`, `typesetdir` and `unpackdir`, as well as all files defined in the `cleanfiles` variable in the same directory as the script. The defaults are `.pdf` files from typesetting (`doc`) and `.zip` files from bundling (`ctan`).

```
$ texlua build.lua ctan
```

Creates an archive of the package and its documentation, suitable for uploading to CTAN. The archive is compiled in `distribdir`, and if the results are successful the resultant `.zip` file is moved into the same directory as the build script. If `packtdszip` is set true then the building process includes a `.tds.zip` file containing the ‘TeX Directory Structure’ layout of the package or bundle. The archive therefore may contain two ‘views’ of the package:

```
abc.zip/
  abc/
    abc.dtx
    abc.ins
    abc.pdf
    README.md
  abc.tds.zip/
    doc/latex/abc/
      abc.pdf
```

```

                                README.md
source/latex/abc/
                                abc.dtx
                                abc.ins
tex/latex/abc/
                                abc.sty

```

The files copied into the archive are controlled by a number of variables. The ‘root’ of the TDS structure is defined by `tdsroot`, which is "latex" by default. Plain users would redefine this to "plain" (or perhaps "generic"), for example. The build process for a `.tds.zip` file currently assumes a ‘standard’ structure in which all extracted files should be places inside the `tex` tree in a single directory, as shown above. If the module includes any BibT<sub>E</sub>X or MakeIndex styles these will be placed in the appropriate subtrees.

The `doc` tree is constructed from:

- all files matched by `demofiles`,
- all files matched by `docfiles`,
- all files matched by `typesetfiles` with their extension replaced with `.pdf`,
- all files matched by `textfiles`,
- all files matched by `bibfiles`.

The `source` tree is constructed from all files matched by `typesetfiles` and `sourcefiles`. The `tex` tree from all files matched by `installfiles`.

Files that should always be excluded from the archive are matched against the `excludefiles` variable; by default this is {"\*~"}, which match Emacs’ autosave files.

Binary files should be specified with the `binaryfiles` variable (default {"\*.pdf", "\*.zip"}); these are added to the zip archive without normalising line endings (text files are automatically converted to Unix-style line endings).

To create the archive, by default the binary `zipexe` is used ("zip") with options `zipopts` (`-v -r -X`). The intermediate build directories `ctandir` and `tdsdir` are used to construct the archive.

```
$ texlua build.lua doc
```

Compiles all documentation files in the `typesetdir` directory. If the compilation is successful the `.pdf` is moved back into the main directory.

The documentation compilation is performed with the `typesetexe` binary (default `pdflatex`), with options `typesetopts`. Additional T<sub>E</sub>X material defined in `typesetcmds` is passed to the document (e.g., for writing `\PassOptionsToClass{l3doc}{letterpaper}`, and so on—note that backslashes need to be escaped in Lua strings).

Files that match `typesetsuppfiles` in the `support` directory (`supportdir`) are copied into the `build/local` directory (`localdir`) for the typesetting compilation process. Additional dependencies listed in the `typesetdeps` variable (empty by default) will also be installed.

If `typesetsearch` is `true` (default), standard `texmf` search trees are used in the typesetting compilation. If set to `false`, *all* necessary files for compilation must be included in the `build/local` sandbox.

```
$ texlua build.lua install
```

Copies all package files (defined by `installfiles`) into the user's home `texmf` tree in the form of the T<sub>E</sub>X Directory Structure.

```
$ texlua build.lua save <name> [<engine>]
```

This command runs through the same execution as `check` for a specific test `<name>.lvt` with optional `<engine>`. If no `<engine>` is specific, this command saves the output of the test to a `.tlg` file. This file is then used in all subsequent checks against the `<name>.lvt` test.

If the `<engine>` is specified (one of `pdftex`, `xetex`, or `luatex`), the saved output is stored in `<name>.<engine>.tlg`. This is necessary if running the test through a different engine produces a different output. A normalisation process is performed when checking to avoid common differences such as register allocation; full details are listed in section 1.6.

```
$ texlua build.lua unpack
```

This is an internal target that is normally not needed on user level. It unpacks all files into the directory defined by `unpackdir`. This occurs before other build commands such as `doc`, `check`, etc.

The unpacking process is performed by executing the `unpackexe` (default `tex`) with options `unpackopts` on all files defined by the `unpackfiles` variable; by default, all files that match `{"*.ins"}`.

If additional support files are required for the unpacking process, these can be enumerated in the `unpacksuppfiles` variable. Dependencies for unpacking are defined with `unpackdeps`.

By default this process allows files to be accessed in all standard `texmf` trees; this can be disabled by setting `unpacksearch` to `false`.

### 1.3 Example build scripts

An example of a standalone build script for a package that uses self-contained `.dtx` files is shown in Figure 1. Here, the `module` only is defined, and since it doesn't use `.ins` files so the variable `unpackfiles` is redefined to run `tex` on the `.dtx` files instead to generate the necessary `.sty` files. There are some PDFs in the repository that shouldn't be part of a CTAN submission, so they're explicitly excluded, and here unpacking is done 'quietly' to minimise console output when building the package. Finally, because this is a standalone package, we assume that `l3build` is installed in the main T<sub>E</sub>X distribution and find the Lua script by searching for it.

An example of a bundle build script for `l3packages` is shown in Figure 2. Note for L<sup>A</sup>T<sub>E</sub>X3 we use a common file to set all build variables in one place, and the path to the

l3build.lua script is hard-coded so we always use our own most recent version of the script. An example of an accompanying module build script is shown in Figure 3.

Under a Unix-like platform, you may wish to run ‘chmod +x build.lua’ on these files, which allows a simpler command line use. Instead of writing

```
texlua build.lua check
```

for example, you would simply write

```
./build.lua check
```

instead. (Or even omit the ./ depending on your path settings.) Windows users can achieve a similar effect by creating a file build.bat as show in Figure 4.

## 1.4 Variables

This section lists all variables defined in the l3build.lua script that are available for customisation.

Variable	Default	Description
module	""	The name of the module.
bundle	""	The name of the bundle in which the module belongs.
ctanpkg	bundle	Name of the bundle on CTAN
modules	{ }	The list of all modules in a bundle (when not auto-detecting)
exclmodules	{ }	Directories to be excluded from automatic module detection
maindir	."	The top level directory for this module or bundle.
supportdir	maindir .. "/support"	Where copies of files to support check/doc compilation are stored.
testfiledir	maindir .. "/testfiles"	Where the tests are.
testsupdir	testfiledir .. "/support"	Where support files for the tests are.

```

1  #!/usr/bin/env texlua
2
3  -- Build script for breqn
4
5  module = "breqn"
6
7  unpackfiles = {"*.dtx"}
8  excludefiles = {"*/breqn-abbr-test.pdf",
9                 "*/eqbreaks.pdf"}
10 unpackopts  = "-interaction=batchmode"
11
12 kpse.set_program_name("kpsewhich")
13 dofile(kpse.lookup("l3build.lua"))

```

Figure 1: The build script for the breqn package.

Variable	Default	Description
localdir	maindir .. "/build/local"	Generated folder where support files are placed to allow “sandboxed” T <sub>E</sub> X runs.
testdir	maindir .. "/build/test"	Generated folder where tests are run.
typesetdir	maindir .. "/build/doc"	Generated folder where typesetting is run.
unpackdir	maindir .. "/build/unpack"	Generated folder where unpacking occurs.
distribdir	maindir .. "/build/distrib"	Generated folder where the archive is created.
ctandir	distribdir .. "/ctan"	Generated folder where files are organised for CTAN.
tdsdir	distribdir .. "/tds"	Generated folder where files are organised for a TDS.
tdsroot	"latex"	Root directory of the TDS structure for the bundle/module to be installed into.
bibfiles	{"*.bst"}	B <sub>I</sub> B <sub>T</sub> <sub>E</sub> X database files.
binaryfiles	{"*.pdf", "*.zip"}	Files to be added in binary mode to zip files.
bstfiles	{"*.bst"}	B <sub>I</sub> B <sub>T</sub> <sub>E</sub> X style files.
checkfiles	{ }	Extra files unpacked purely for tests
checksuppfiles	{ }	Files needed for performing regression tests.
cmdchkfiles	{ }	Files need to perform command checking (l3doc-based documentation only).
cleanfiles	{"*.log", "*.pdf", "*.zip"}	Files to delete when cleaning.
demofiles	{ }	Files which show how to use a module.
docfiles	{ }	Files which are part of the documentation but should not be typeset.
excludefiles	{"*-"}	Files to ignore entirely (default for Emacs backup files).
installfiles	{"*.sty"}	Files to install to the T <sub>E</sub> X tree and similar tasks.
makeindexfiles	{"*.ist"}	MakeIndex files to be included in a TDS-style zip
sourcefiles	{"*.dtx", "*.ins"}	Files to copy for unpacking.
textfiles	{"*.md", "*.txt"}	Plain text files to send to CTAN as-is.
typesetfiles	{"*.dtx"}	Files to typeset for documentation.
typesetsuppfiles	{ }	Files needed to support typesetting when “sandboxed”.
unpackfiles	{"*.ins"}	Files to run to perform unpacking.
unpacksuppfiles	{ }	Files needed to support unpacking when “sandboxed”.
lvtext	".lvt"	Extension of test files.
tlgext	".tlg"	Extension of test file output.
logext	".log"	Extension of checking output, before processing it into a .tlg.
checkdeps	{ }	List of build unpack dependencies for checking.
typesetdeps	{ }	...for typesetting docs.
unpackdeps	{ }	...for unpacking.
checkengines	{"pdftex", "xetex", "luatex"}	Engines to check with <code>check</code> by default.
stdengine	"pdtex"	Engine to generate .tlg file from.
checkformat	"latex"	Format to use for tests.
typesetexe	"pdflatex"	Executable for compiling doc(s).
unpackexe	"tex"	Executable for running unpack.



Variable	Default	Description
<code>zipexe</code>	"zip"	Executable for creating archive with <code>ctan</code> .
<code>checkopts</code>	"-interaction=batchmode"	Options based to engine when running checks.
<code>cmdchkopts</code>	"-interaction=batchmode"	Options based to engine when running command checks.
<code>typesetopts</code>	"-interaction=nonstopmode"	Options based to engine when typesetting.
<code>unpackopts</code>	"	Options based to engine when unpacking.
<code>zipopts</code>	"-v -r -X"	Options based to zip program.
<code>checksearch</code>	true	Look in <code>tds</code> dirs for checking?
<code>typesetsearch</code>	true	Look in <code>tds</code> dirs for typesetting docs?
<code>unpacksearch</code>	true	Look in <code>tds</code> dirs for unpacking?
<code>glossarystyle</code>	"gglo.ist"	MakeIndex style file for glossary/changes creation
<code>indexstyle</code>	"gind.ist"	MakeIndex style for index creation
<code>biberexe</code>	"biber"	Biber executable
<code>biberopts</code>	"	Biber options
<code>bibtexexe</code>	"bibtex8"	BIB <sub>T</sub> E <sub>X</sub> executable
<code>bibtexopts</code>	"-W"	BIB <sub>T</sub> E <sub>X</sub> options
<code>makeindexexe</code>	"makeindex"	MakeIndex executable
<code>makeindexopts</code>	"	MakeIndex options
<code>checkruns</code>	1	How many times to run a check file before comparing the log.
<code>packtdszip</code>	false	Build a TDS-style zip file for CTAN?
<code>scriptname</code>	"build.lua"	Name of script used in dependencies.
<code>typesetcmds</code>	"	Instructions to be passed to T <sub>E</sub> X when doing typesetting.

## 1.5 Dependencies

If you have multiple packages that are developed separately but still interact in some way, it's often desirable to integrate them when performing regression tests. For L<sup>A</sup>T<sub>E</sub>X3, for example, when we make changes to `l3kernel` it's important to check that the tests for `l3packages` still run correctly, so it's necessary to include the `l3kernel` files in the build process for `l3packages`.

In other words, `l3packages` is *dependent* on `l3kernel`, and this is specified in `l3build` by setting appropriately the variables `checkdeps`, `typesetdeps`, and `unpackdeps`. The relevant parts of the L<sup>A</sup>T<sub>E</sub>X3 repository is structured as the following.

```

l3/
  l3kernel/
    build.lua
    expl3.dtx
    expl3.ins
    ...
    testfiles/
  l3packages/

```

```

1  #!/usr/bin/env texlua
2
3  -- Build script for LaTeX3 "l3packages" files
4
5  -- Identify the bundle: there is no module as this is the "driver"
6  bundle = "l3packages"
7
8  -- Location of main directory: use Unix-style path separators
9  maindir = ".."
10
11 -- Load the common build code: this is the one place that a path
12 -- needs to be hard-coded
13 dofile (maindir .. "/l3build/l3build-config.lua")
14 dofile (maindir .. "/l3build/l3build.lua")

```

Figure 2: The build script for the l3packages bundle.

```

1  #!/usr/bin/env texlua
2
3  -- Build script for LaTeX3 "xparse" files
4
5  -- Identify the bundle and module:
6  bundle = "l3packages"
7  module = "xparse"
8
9  -- Location of main directory: use Unix-style path separators
10 -- Should match that defined by the bundle.
11 maindir = "../.."
12
13 -- Load the common build code: this is the one place that a path
14 -- needs to be hard-coded
15 dofile (maindir .. "/l3build/l3build-config.lua")
16 dofile (maindir .. "/l3build/l3build.lua")

```

Figure 3: The build script for the xparse module.

```

1  @echo off
2  texlua build.lua %*

```

Figure 4: Windows batch file wrapper for running the build process.

```

        build.lua
        xparse/
            build.lua
            testfiles/
            xparse.dtx
            xparse.ins
    support/

```

For L<sup>A</sup>T<sub>E</sub>X3 build files, `maindir` is defined as top level folder `l3`, so all support files are located here, and the build directories will be created there. To set `l3kernel` as a dependency of `l3package`, within `l3packages/xparse/build.lua` the equivalent of the following is set:

```

maindir = "../.."
checkdeps = {maindir .. "/l3kernel"}

```

This ensures that the `l3kernel` code is included in all processes involved in unpacking and checking and so on. The name of the script file in the dependency is set with the `scriptname` variable; by default these are `"build.lua"`.

## 1.6 Output normalisation

To allow test files to be used between different systems (*e.g.* when multiple developers are involved in a project), the log files are normalised before comparison during checking. This removes some system-dependent data but also some variations due to different engines. This normalisation consists of two parts: removing (“ignoring”) some lines and modifying others to give consistent test. Currently, the following types of line are ignored:

- Lines before the `\START`, after the `\END` and within `\OMIT`/`\TIMO` blocks
- Entirely blank lines, including those consisting only of spaces.
- Lines containing file dates in format `<yyy>/<mm>/<dd>`.
- Lines starting `\openin` or `\openout`.

Modifications made in lines are:

- Removal of the name of the test file itself.
- Removal of the `pdftex.map` load information given during first page shipout.
- Removal spaces at the start of lines.
- Removal of `./` at start of file names.
- Standardisation of the list of units known to T<sub>E</sub>X (pdfT<sub>E</sub>X and LuaT<sub>E</sub>X add a small number of additional units which are not known to T<sub>E</sub>X90 or X<sub>E</sub>L<sub>A</sub>T<sub>E</sub>X).
- Standardisation of `\csname\endcsnameL` to `\csname\endcsname` (the former is formally correct, but the latter was produced for many years due to a T<sub>E</sub>X bug).

- Conversion of `on line <number>` to `on line ...` to allow flexibility in changes to test files.

- 

LuaTeX makes several additional changes to the log file. As normalising these may not be desirable in all cases, they are handled separately. When creating LuaTeX-specific test files (either with LuaTeX as the standard engine or saving a LuaTeX-specific `.tlg` file) no further normalisation is undertaken. On the other hand, for cross-engine comparison the following normalisation is applied:

- Removal of additional (unused) `\discretionary` points.
- Removal of `U+...` notation for missing characters.
- Removal of `display` for display math boxes (included by TeX90/pdfTeX/X<sub>Y</sub>TeX).
- Removal of Omega-like `direction` TLT information.
- Removal of additional whatsit containing local paragraph information (`\localinterlinepenalty`, *etc.*).
- Rounding of glue set to four decimal places (glue set may be slightly different in LuaTeX compared to other engines).
- Conversion of low chars (1 to 31) to `^^` notation.

## 1.7 Generating test files with DocStrip

It is possible to pack tests inside source files. Tests generated during the unpacking process will be available to the `check` and `save` commands as if they were stored in the `testfiledir`. Any explicit test files inside `testfiledir` take priority over generated ones with the same names.

## 2 Writing test files

Test files are written in a TeX dialect using the support file `regression-test.tex`, which should be `\input` at the very beginning of each test. Additional customisations to this driver can be included in a local `regression-test.cfg` file, which will be loaded automatically if found.

The macros loaded by `regression-test.tex` set up the test system and provide a number of commands to aid the production of a structured test suite. The basis of the test suite is to output material into the `.log` file, from which a normalised test output (`.tlg`) file is produced by the build command `save`. A number of commands are provided for this; they are all written in uppercase to help avoid possible conflicts with other package commands.

## 2.1 Metadata and structural commands

Any commands that write content to the `.log` file that should be ignored can be surrounded by `\OMIT ... \TIMO`. At the appropriate location in the document where the `.log` comparisons should start (say, after `\begin{document}`), the test suite must contain the `\START` macro. The test should then include `\AUTHOR{authors details}` in case a test file fails in the future and needs to be re-analysed.

Some additional diagnostic information can then be included as metadata for the conditions of the test. The desired format can be indicated with `\FORMAT{format name}`, and any packages or classes loaded can be indicated with

```
\CLASS[options]{class name, version}
\PACKAGE[options]{package name, version}
```

These do not provide information that is useful for automated checking; after all, packages change their version numbers frequently. Rather, including this information in a test indicates the conditions under which the test was definitely known to pass at a certain time in the past.

The `\END` command signals the end of the test (but read on). Some additional diagnostic information is printed at this time to debug if the test did not complete ‘properly’ in terms of mismatched brace groups or `\if... \fi` groups.

In a  $\text{\LaTeX}$  document, `\end{document}` will implicitly call `\END` at the very end of the compilation process. If `\END` is used directly (replacing `\end{document}` in the test), the compilation will halt almost immediately, and various tasks that `\end{document}` usually performs will not occur (such as potentially writing to the various `.toc` files, and so on). This can be an advantage if there is additional material printed to the log file in this stage that you wish to ignore, but it is a disadvantage if the test relies on various auxiliary data for a subsequent typesetting run. (See the `checkruns` variable for how these tests would be test up.)

## 2.2 Commands to help write tests

A simple command `\CHECKCOMMAND\<macro>` is provided to check whether a particular `\<macro>` is defined, undefined, or equivalent to `\relax`. This is useful to flag either that internal macros are remaining local to their definitions, or that defined commands definitely are defined, or even as a reminder that commands you intend to define in a future package need to be tested once they appear.

`\TYPE` is used to write material to the `.log` file, like  $\text{\LaTeX}$ ’s `\typeout`, but it allows ‘long’ input. The following commands are defined to use `\TYPE` to output strings to the `.log` file.

- `\SEPARATOR` inserts a long line of `=` symbols to break up the log output.
- `\NEWLINE` inserts a linebreak into the log file.
- `\TRUE`, `\FALSE`, `\YES`, `\NO` output those strings to the log file.
- `\ERROR` is *not* defined but is commonly used to indicate a code path that should never be reached.

- The `\TEST{<title>}{<contents>}` command surrounds its `<contents>` with some `\SEPARATORS` and a `<title>`.
- `\TESTEXP` surrounds its contents with `\TYPE` and formatting to match `\TEST`; this can be used as a shorthand to test expandable commands.
- TODO: would a `\TESTFEXP` command (based on `\romannumeral` expansion) be useful as well?

An example of some of these commands is shown following.

```
\TEST{bool_set,~lazy~evaluation}
{
  \bool_set:Nn \l_tmpa_bool
  {
    \int_compare_p:nNn 1=1
    && \bool_if_p:n
    {
      \int_compare_p:nNn 2=3 ||
      \int_compare_p:nNn 4=4 ||
      \int_compare_p:nNn 1=\ERROR % is skipped
    }
    && \int_compare_p:nNn 2=2
  }
  \bool_if:NTF \l_tmpa_bool \TRUE \FALSE
}
```

This test will produce the following in the output.

```
=====
TEST 8: bool_set, lazy evaluation
=====
TRUE
=====
```

(Only if it's the eighth test in the file of course, and assuming `expl3` coding conventions are active.)

## 2.3 Showing box content

The commands introduced above are only useful for checking algorithmic or logical correctness. Many packages should be tested based on their typeset output instead; `TEX` provides a mechanism for this by printing the contents of a box to the log file. The `regression-test.tex` driver file sets up the relevant `TEX` parameters to produce as much output as possible when showing box output.

A plain `TEX` example of showing box content follows.

```

\input regression-test.tex\relax
\START
\setbox0=\hbox{\rm hello \it world $a=b+c$}
\showbox0
\END

```

This produces the output shown in Figure 5 (left side). It is clear that if the definitions used to typeset the material in the box changes, the log output will differ and the test will no longer pass.

The equivalent test in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> using `expl3` is similar.

```

\input{regression-test.tex}
\documentclass{article}
\usepackage{expl3}
\START
\ExplSyntaxOn
\box_new:N \l_tmp_box
\hbox_set:Nn \l_tmp_box {hello~ \emph{world}~ $a=b+c$}
\box_show:N \l_tmp_box
\ExplSyntaxOff
\END

```

The output from this test is shown in Figure 5 (right side). There is marginal difference (mostly related to font selection and different logging settings in L<sup>A</sup>T<sub>E</sub>X) between the plain and `expl3` versions.

When examples are not self-contained enough to be typeset into boxes, it is possible to ask T<sub>E</sub>X to output the entire contents of a page. Insert `\showoutput` for L<sup>A</sup>T<sub>E</sub>X or set `\tracingoutput` positive for plain T<sub>E</sub>X; ensure that the test ends with `\newpage` or equivalent because T<sub>E</sub>X waits until the entire page is finished before outputting it.

TODO: should we add something like `\TRACEPAGES` to be format-agnostic here? Should this perhaps even be active by default?

## 2.4 Typesetting documentation

As part of the overall build process, `l3build` will create PDF documentation as described earlier. The standard build process for PDFs will attempt to run Biber, BibT<sub>E</sub>X and MakeIndex as appropriate (the exact binaries used are defined by "`biber`", "`bibtex8`" and "`makeindex`"). However, there is no attempt to create an entire PDF creation system in the style of `latexmk` or similar.

For package authors who have more complex requirements than those covered by the standard set up, the Lua script offers the possibility for customisation. The Lua function `typeset` may be defined before reading `l3build.lua` and should take one argument, the name of the file to be typeset. Within this function, the auxiliary Lua functions `biber`, `bibtex`, `makeindex` and `tex` can be used, along with custom code, to define a PDF typesetting pathway. The functions `biber` and `bibtex` take a single argument: the name of the file to work with *minus* any extension. The `tex` takes as an argument the

```

> \box0=
\hbox(6.94444+0.83333)x90.56589
.\tenrm h
.\tenrm e
.\tenrm l
.\tenrm l
.\tenrm o
.\glue 3.33333 plus 1.66666 minus 1.11111
.\tenit w
.\tenit o
.\tenit r
.\tenit l
.\tenit d

.\glue 3.57774 plus 1.53333 minus 1.0222
.\mathon
.\teni a
.\glue(\thickmuskip) 2.77771 plus 2.77771
.\tenrm =
.\glue(\thickmuskip) 2.77771 plus 2.77771
.\teni b
.\glue(\medmuskip) 2.22217 plus 1.11108 minus 2.22217
.\tenrm +
.\glue(\medmuskip) 2.22217 plus 1.11108 minus 2.22217
.\teni c
.\mathoff

```

```

! OK.
l.9 \showbox0

```

```

> \box71=
\hbox(6.94444+0.83333)x91.35481
.\OT1/cmr/m/n/10 h
.\OT1/cmr/m/n/10 e
.\OT1/cmr/m/n/10 l
.\OT1/cmr/m/n/10 l
.\OT1/cmr/m/n/10 o
.\glue 3.33333 plus 1.66666 minus 1.11111
.\OT1/cmr/m/it/10 w
.\OT1/cmr/m/it/10 o
.\OT1/cmr/m/it/10 r
.\OT1/cmr/m/it/10 l
.\OT1/cmr/m/it/10 d
.\kern 1.03334
.\glue 3.33333 plus 1.66666 minus 1.11111
.\mathon
.\OML/cmm/m/it/10 a
.\glue(\thickmuskip) 2.77771 plus 2.77771
.\OT1/cmr/m/n/10 =
.\glue(\thickmuskip) 2.77771 plus 2.77771
.\OML/cmm/m/it/10 b
.\glue(\medmuskip) 2.22217 plus 1.11108 minus 2.22217
.\OT1/cmr/m/n/10 +
.\glue(\medmuskip) 2.22217 plus 1.11108 minus 2.22217
.\OML/cmm/m/it/10 c
.\mathoff

```

```

! OK.
<argument> \l_tmp_box

```

```

l.12 \box_show:N \l_tmp_box

```

Figure 5: Output from displaying the contents of a simple box to the log file, using plain  $\text{\TeX}$  (left) and  $\text{\exp\l3}$  (right). Some blank lines have been added to the plain  $\text{\TeX}$  version to help with the comparison.



full name of the file. The most complex function `makeindex` requires the name, input extension, putput extension, log extension and style name. For example, Figure 6 shows a simple script which might apply to a case where multiple `BIBTEX` runs are needed (perhaps where citations can appear within other references).

## Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols		
<code>\&lt;macro&gt;</code>	.....	<u>13</u> , 13
A		
<code>\AUTHOR</code>	.....	<u>12</u>
C		
<code>\CHECKCOMMAND</code>	.....	<u>13</u>
<code>\CLASS</code>	.....	<u>12</u>
E		
<code>\END</code>	.....	<u>11</u>
<code>\ERROR</code>	.....	<u>13</u>
F		
<code>\FALSE</code>	.....	<u>13</u>

```

1  #!/usr/bin/env texlua
2
3  -- Build script with custom PDF route
4
5  module = "mymodule"
6
7  function typeset (file)
8      local name = string.match (file, "^(.*)%.") or name
9      local errorlevel = tex (file)
10     if errorlevel == 0 then
11         -- Return a non-zero errorlevel if anything goes wrong
12         errorlevel = (
13             bibtex (name) +
14             tex (file) +
15             bibtex (name) +
16             tex (file) +
17             tex (file)
18         )
19     end
20     return errorlevel
21 end
22
23 kpse.set_program_name("kpsewhich")
24 dofile(kpse.lookup("l3build.lua"))

```

Figure 6: A customised PDF creation script.

<code>\fi</code> .....	13	<code>\romannumeral</code> .....	13
<code>\FORMAT</code> .....	12		
		<b>S</b>	
<b>I</b>		<code>\SEPARATOR</code> .....	13, 13
<code>\if</code> .....	13	<code>\showoutput</code> .....	15
		<code>\START</code> .....	11
<b>N</b>			
<code>\NEWLINE</code> .....	13	<b>T</b>	
<code>\newpage</code> .....	15	<code>\TEST</code> .....	13, 13
<code>\NO</code> .....	13	<code>\TESTEXP</code> .....	13
		<code>\TESTFEXP</code> .....	13
<b>O</b>		<code>\TIMO</code> .....	11
<code>\OMIT</code> .....	11	<code>\TRACEPAGES</code> .....	15
<code>\openin</code> .....	11	<code>\tracingoutput</code> .....	15
<code>\openout</code> .....	11	<code>\TRUE</code> .....	13
		<code>\TYPE</code> .....	13, 13, 13
<b>P</b>		<code>\typeout</code> .....	13
<code>\PACKAGE</code> .....	12		
		<b>Y</b>	
<b>R</b>		<code>\YES</code> .....	13
<code>\relax</code> .....	13		